


IE2

TECHNICAL DATASHEET 3 PHASE INDUCTION MOTOR




Sr No	Parameter	Unit	Data
Product Specifications			
1	Rated Output	kW	1.1
2	Number of Poles	No	8
3	Frame Designation		KM100L
4	Product Code		KM2.1T10.DIC.B14.TSS
5	Mounting		B14
Electrical			
6	Type of Duty		Continuous S1
7	Rated Voltage	V	415 $\pm$ 10%
8	Rated Frequency	Hz	50 $\pm$ 5%
9	Rated Speed	RPM	700
10	Rated Current	A	3.43
11	Method of Starting		Direct On Line
12	Starting Current (SCC)	% of FLA	500
13	Rated Torque	Kg-m	1.53
14	Starting Torque (STT)	% of FLT	200
15	Maximum Torque (POT)	% of FLT	225
16	Efficiency at 100% / 75% / 50% load	%	70.8 / 70.8/ 68
17	Power factor at 100% / 75% / 50% load		0.63 / 0.5 / 0.38
18	Thermal Withstand Time (Hot)	s	8
19	Thermal Withstand Time (Cold)	s	16
20	Thermal Time Constant (Stator)	min	30
21	Connection / Number of Terminals		Star / 6
22	Permissible Starts/hour (Hot/Cold)	Nos	2/3
23	Insulation Class / Thermal Limit		F/B
24	Winding Treatment		VPI, Dual Coat Copper Wire
Mechanical			
25	Degree of Protection		IP55
26	Enclosure / MOC /Method of Cooling		TEFC / CI/ IC411
27	Bearing DE/NDE		6206ZZ/6205ZZ
28	Type of Coupling		Direct/Flexible
29	Noise Level		As per IS12065
30	Vibration Level		As per IS12075
31	Moment of Inertia GD ²	kg-m ²	0.0382
32	Position of Terminal Box		TOP
33	Maximum Cable Size		2X3CX6 mm ²
34	Direction of Rotation		Bidirectional (Default: CW from DE)
35	Paint Shade		RAL 7046- Telegrey
36	Net weight	kg	32
37	Accessories		NA
Enviromental			
38	Ambient Temperature /Temperature Rise	°C	50 / 70 (By resistance method)
39	Altitude Above MSL	m	$\leq$ 1000
Notes: All performance data shall be subject to tolerances as per IS15999/IEC 60034. Applicable Standards:IS 12615-2018, IS 15999-1			
Customer		PO No./ Enq. No	
		Date	
Checked	BMD	17-05-2023	
Approved	SSN	17-05-2023	Document No: KM2-001 Rev.0
KIRLOSKAR OIL ENGINES LTD. ELECTRIC MOTORS			

PERFORMANCE CURVE




kW	1.1	Customer	
Pole	8	PO No / Enq. No	
Frame	KM100L	Date	
Mounting	B14	Product Code	KM2.1T10.DIC.B14.TSS
Checked	BMD	17-05-2023	
Approved	SSN	17-05-2023	Document No KM2-002 Rev. 0

KIRLOSKAR OIL ENGINES LTD.
ELECTRIC MOTORS



GENERAL ARRANGEMENT DRAWING FOR TEFC 3 PHASE INDUCTION MOTOR



FRAME	FACE FIXING					OVER ALL		
	MTol	NTol	P	S	T	AC	L	AD
KM100L	130	110.013/109.991	160	M8X10	3.5	198	410	145

D END SHAFT EXTENSION AND KEY						
D TOL.	E	ED	F TOL.	GD TOL.	G	Y
28.009/27.996	60	50	8/7.964	7.0/6.9	24.0/23.9	M10X24

kW	PRODUCT CODE
	8 POLE
0.75	KM2.0T75.DIC.B14.TSS
1.1	KM2.1T10.DIC.B14.TSS

NOTES:

- ONE EARTHING TERMINAL IS PROVIDED INSIDE MAIN TERMINAL BOX.
- * 80mm MINIMUM DISTANCE TO BE MAINTAINED FOR EFFICIENT COOLING OF THE MOTOR.
- * TOLERANCES ON MANDATORY DIMENSIONS ARE AS PER IS:2223/IEC:60072

RINGED DIMENSIONS ARE AS PER IS:2223/IEC:60072-1


ALL DIMENSIONS ARE IN mm,

	NAME	DATE	kW	REFER TABLE	FRAME	KM100L
DRAWN	SGS	19/08/2022	POLE	REFER TABLE	MOUNTING	B14 (HORIZONTAL FACE)
CHECKED	SGS	19/08/2022	PRODUCT CODE	REFER TABLE	CUSTOMER	
APPROVED	SSN	19/08/2022	MAX. CABLE SIZE	2RX3CX6MM ²	PO NO	
			PROJECT		CLIENT	

KIRLOSKAR OIL ENGINES LTD.
ELECTRIC MOTORS

DO NOT SCALE
FORMAT NO.:KM-GA-2021 R0

DRAWING NO
KM100LB14TSR0



ALL DIMENSIONS ARE IN mm

	NAME	DATE	kW		FRAME	KM100L
DRAWN	SGS	24/12/2021	POLE		CUSTOMER	
CHECKED	SGS	24/12/2021	PRODUCT CODE		PO NO	
APPROVED	SSN	24/12/2021	MAX. CABLE SIZE	2RX3CX6MM ²	CLIENT	
			CABLE ENTRY	M20X1.5P-2NOS.	PROJECT	
KIRLOSKAR OIL ENGINES LTD. ELECTRIC MOTORS				DO NOT SCALE FORMAT NO.:KM-TB-2021 RO		DRAWING NO KM100TBR1