


IE2

TECHNICAL DATASHEET
3 PHASE INDUCTION MOTOR - FIRE FIGHTING



Sr No	Parameter	Unit	Data
Product Specifications			
1	Rated Output	kW	37
2	Number of Poles	No	2
3	Frame Designation		KM180L
4	Product Code		KM2.37T0.AMC.B03.TSN
5	Mounting		B3
Electrical			
6	Type of Duty		Continuous S1
7	Rated Voltage	V	415 ±10%
8	Rated Frequency	Hz	50 ±5%
9	Rated Speed	RPM	2945
10	Rated Current	A	63
11	Method of Starting		Direct On Line
12	Starting Current (SCC)	% of FLA	650
13	Rated Torque	Kg-m	12.24
14	Starting Torque (STT)	% of FLT	200
15	Maximum Torque (POT)	% of FLT	250
16	Efficiency at 100% / 75% / 50% load	%	92.5 / 91/ 89
17	Power factor at 100% / 75% / 50% load		0.88 / 0.85 / 0.8
18	Thermal Withstand Time (Hot)	s	10
19	Thermal Withstand Time (Cold)	s	20
20	Thermal Time Constant (Stator)	min	40
21	Connection / Number of Terminals		Delta / 6
22	Permissible Starts/hour (Hot/Cold)	Nos	2/3
23	Insulation Class / Thermal Limit		F/F
24	Winding Treatment		VPI, Dual Coat Copper Wire
Mechanical			
25	Degree of Protection		IP55
26	Enclosure / MOC /Method of Cooling		TEFC / CI/ IC411
27	Bearing DE/NDE		6310ZZ/6310ZZ
28	Type of Coupling		Direct/Flexible
29	Noise Level		As per IS12065
30	Vibration Level		As per IS12075
31	Moment of Inertia GD ²	kg-m ²	0.790
32	Position of Terminal Box		TOP
33	Maximum Cable Size		2X3CX50 mm ²
34	Direction of Rotation		Bidirectional (Default: CW from DE)
35	Paint Shade		RAL 3001
36	Net weight	kg	209
37	Accessories		NA
Enviromental			
38	Ambient Temperature /Temperature Rise	°C	50 / 95 (By resistance method)
39	Altitude Above MSL	m	≤ 1000
Notes: All performance data shall be subject to tolerances as per IS15999/IEC 60034. Applicable Standards:IS 12615-2018, IS 15999-1			
Customer		PO No./ Enq. No	
		Date	
Checked	BMD	22/10/2022	
Approved	SSN	22/10/2022	Document No: KM2-001 Rev.0
KIRLOSKAR OIL ENGINES LTD. ELECTRIC MOTORS			


PERFORMANCE CURVE




kW	37	Customer	
Pole	2	PO No / Enq. No	
Frame	KM180L	Date	
Mounting	B3	Product Code	KM2.37T0.AMC.B03.TSN
Checked	BMD	22/10/2022	
Approved	SSN	22/10/2022	Document No KM2-002 Rev. 0

KIRLOSKAR OIL ENGINES LTD.

ELECTRIC MOTORS



GENERAL ARRANGEMENT DRAWING FOR TEFC 3 PHASE INDUCTION MOTOR



FRAME	FOOT FIXING									OVER ALL			
	A	B	C	H TOL.	AA	AB	BA	BB	K TOL.	AC	L	HD	HA
KM180L	279	279	121	180/179.5	75	360	--	335	15/15.5	352	715	460	28

D END SHAFT EXTENSION AND KEY						
D TOL.	E	ED	F TOL.	GD TOL.	G	Y
48.018/48.002	110	110	14/13.957	9.0/8.9	42.5/42.3	M16X45

NOTES:

- * 100mm MINIMUM DISTANCE TO BE MAINTAINED FOR EFFICIENT COOLING OF THE MOTOR.
- * TOLERANCES ON MANDATORY DIMENSIONS ARE AS PER IS:1231/IEC:60072

RINGED DIMENSIONS ARE AS PER IS:1231/IEC:60072


ALL DIMENSIONS ARE IN mm,

	NAME	DATE	kW	37	FRAME	KM180L
DRAWN	KSK	14/10/2022	POLE	2	MOUNTING	B3 (HORIZONTAL FOOT)
CHECKED	SGS	14/10/2022	PRODUCT CODE	KM2.37T0.AMC.B03.TSN	CUSTOMER	
APPROVED	SSN	14/10/2022	MAX. CABLE SIZE	2RX3CX50MM ²	PO NO	
			PROJECT		CLIENT	

KIRLOSKAR OIL ENGINES LTD.
ELECTRIC MOTORS



DO NOT SCALE
FORMAT NO.:KM-GA-2021 R0

DRAWING NO
KM180LB3TSFFR0



TERMINAL ARRANGEMENT DRAWING

kirloskar
motors



ALL DIMENSIONS ARE IN mm

	NAME	DATE	kW		FRAME	KM180L
DRAWN	KSK	17/10/2022	POLE		CUSTOMER	
CHECKED	SGS	17/10/2022	PRODUCT CODE		PO NO	
APPROVED	SSN	17/10/2022	MAX. CABLE SIZE	2RX3CX50MM ²	CLIENT	
			CABLE ENTRY	M40X1.5P-2NOS.	PROJECT	
KIRLOSKAR OIL ENGINES LTD.				DO NOT SCALE	DRAWING NO	
ELECTRIC MOTORS				FORMAT NO.:KM-TB-2021 R0	KM180LTBFFR0	